



F115BETX/FL115BETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F115BETX	FL115BETX
MOTOR		
Displacement (cc)	1832	1832cm3
Architecture	L4	L4
Bore x Stroke (mm)	81.0 X 88.9	81.0 X 88.9
Full throttle operating range (tr/min)	5300-6300	5300-6300
Fuel	Wet Sump	Wet Sump
Fuel consumption (L/h-tr/min)	38.9 L/h @5800 r/min	38.9 L/h @5800 r/min
Lubrication system	Unleaded	Unleaded
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Reduction ratio	10.0 :1	10.0 :1
Number of Displacement	-	-
Maximum Power (Kw)	-	-
Ignition System	Electronic ignition (TCI)	Electronic ignition (TCI)
Gear Ratio	-	-
Steering Control	-	-
Reverse direction	-	-
Trim method (positions)	-	-
Engine Type	In-line 4	In-line 4
Start-up	Electric with Prime Start™	Electric with Prime Start™
Max.Prop Shaft Horsepower (Kw)	84.6 (115 hp)	84.6 kW (115 hp)
MORE		
Control	Remote Control	Remote Control
Alternator	35 A	35 A
Propeller Rotation	Clockwise	Clockwise
DIMENSIONS		
Engine Oil Capacity (L)	-	0.760L
Oil capacity (L)	3.2 L / 3.0 L	3.2 L
Engine transom height (mm)	X : 643 (25.3 inch)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	185	179

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

