



F250HETX/FL250HETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F250HETX	FL250HETX
MOTOR		
Gear Ratio	2.00 (26/13)	2.00 (26/13)
Ignition System	Electronic Ignition (TCI)	Electronic Ignition (TCI)
Maximum Power (Kw)	183,9	183,9
Number of Displacement	6	6
Reduction ratio	9.9 :1	9.9 :1
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Bore x Stroke (mm)	94.0 X 80.5	94.0 X 80.5
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	75.6 L/h @5500 r/min	75.6 L/h @5500 r/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	5000-6000	5000-6000
Displacement (cc)	3352	3352
Architecture	V6	V6
Engine Type	4-stroke engine - V6	4-stroke engine - V6
Start-up	Electric with Prime Start™	Electric with Prime Start™
Max.Prop Shaft Horsepower (Kw)	183.9 (250 hp)	183.9 (250 hp)
MORE		
Propeller Rotation	Clockwise	Counter clockwise
Alternator	46 A	46 A
Control	Remote Control	Remote Control
DIMENSIONS		
Engine Oil Capacity (L)	4.7 L / 4.5 L	4.7 L / 4.5 L
Engine transom height (mm)	X : 643 (25.3 inch)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	289	289

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

