



## F250HETX/FL250HETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F250HETX
<b>MOTOR</b>	
Gear Ratio	2.00 (26/13)
Ignition System	Electronic Ignition (TCI)
Maximum Power (Kw)	183,9
Number of Displacement	6
Reduction ratio	9.9 :1
Power system	Electronic Injection (EFI)
Bore x Stroke (mm)	94.0 X 80.5
Lubrication system	Unleaded
Fuel consumption (L/h-tr/min)	75.6 L/h @5500 r/min
Fuel	Wet Sump
Full throttle operating range (tr/min)	5000-6000
Displacement (cc)	3352
Architecture	V6
Engine Type	4-stroke engine - V6
Start-up	Electric with Prime Start™
Max.Prop Shaft Horsepower (Kw)	183.9 (250 hp)
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	46 A
Control	Remote Control
<b>DIMENSIONS</b>	
Engine Oil Capacity (L)	4.7 L / 4.5 L
Engine transom height (mm)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	289

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

