



The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

## E115AETL



TECHNICAL CHARACTERISTICS	E115AETL
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	5.7 :1
Start-up	Electric
Power system	2 Dual Throat Carburetors
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	47 l/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	84.6 KW (115 hp)
Bore x Stroke (mm)	90.0 X 68.0
Architecture	V4
Displacement (cc)	1730
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	10A
Control	Remote Control
<b>DIMENSIONS</b>	
Engine transom height (mm)	L : 516 (20.3 in)
Dry weight with propeller (kg)	160
<b>EQUIPMENTS</b>	
Service kit assy.	✓
Fuel Pipe Comp.	✓
Remocon Control	✓
15ft Cable Remocon	✓
Tachometer	✓
Trim Meter	✓
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	13

Always wear a helmet, eye protection and protective proper clothing.  
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

