



The "ENDURO" engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

E15DMHL



TECHNICAL CHARACTERISTICS	E15DMHL
MOTOR	
Engine Type	In-line 2
Reduction ratio	7.0 :1
Start-up	Manual
Power system	1 Carburetor
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	7.7 L/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	11.0 (15 hp)
Bore x Stroke (mm)	56.0 x 50.0
Architecture	L2
Displacement (cc)	246
MORE	
Propeller Rotation	Clockwise
Alternator	80 W (optional)
Control	Tiller handle
DIMENSIONS	
Engine transom height (mm)	L : 568 (22.4 in)
Dry weight with propeller (kg)	41
EQUIPMENTS	
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
REGULAR PROPELLER (3 blades)	
Material	ALUMINUM
Diameter	9 1/4

Always wear a helmet, eye protection and protective proper clothing.
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

