



The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

## E15DMHL



TECHNICAL CHARACTERISTICS	E15DMHL
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	7.0 :1
Start-up	Manual
Power system	1 Carburetor
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	7.7 L/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	11.0 (15 hp)
Bore x Stroke (mm)	56.0 x 50.0
Architecture	L2
Displacement (cc)	246
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	80 W (optional)
Control	Tiller handle
<b>DIMENSIONS</b>	
Engine transom height (mm)	L : 568 (22.4 in)
Dry weight with propeller (kg)	41

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

