



The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

## E75BMHDL



TECHNICAL CHARACTERISTICS	E75BMHDL
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	4.5 :1
Start-up	Manual
Power system	3 Carburetors
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	34.0 L/h @5500 r/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	55.2 (75 hp)
Bore x Stroke (mm)	82.0 X 72.0
Architecture	L3
Displacement (cc)	1140
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	10 A
Control	Tiller handle
<b>DIMENSIONS</b>	
Engine transom height (mm)	L : 521 mm (20.5 in)
Dry weight with propeller (kg)	121

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

