



F250HETU/FL250HETU

The Africa 4-stroke range, born from monitoring and the long Yamaha experience, has been specially developed to correspond to local conditions of use, such as muddy water or low octane fuels. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F250HETU	FL250HETU
MOTOR		
Engine Type	In-line 4	In-line 4
Ignition System	Electronic Ignition (TCI)	Electronic Ignition (TCI)
Reduction ratio	94.0 X 80.5	94.0 X 80.5
Start-up	Electric with Prime Start™	Electric with Prime Start™
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	75.6 L/h @5500 r/min	75.6 L/h @5500 r/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	5000-6000	5000-6000
Max.Prop Shaft Horsepower (Kw)	183.9 (250 hp)	183.9 (250 hp)
Bore x Stroke (mm)	94.0 X 80.5	94.0 X 80.5
Architecture	V6	V6
Displacement (cc)	3352	3352
MORE		
Propeller Rotation	Sens Horaire	Counter Clockwise
Alternator	46 A	46 A
Control	Remote Control	Remote Control
DIMENSIONS		
Dry weight with propeller (kg)	289	289
Engine transom height (mm)	U : 770 (30.3 inch)	U : 770 (30.3 inch)
Oil capacity (L)	4.7 L/ 4.5 L	4.7 L/ 4.5 L
EQUIPMENT		
Service kit assy.	✓	✓
Remocon Control	✓	✓
Cable end, Remote control	✓	-
Panel Switch	✓	✓
REGULAR PROPELLER (3 blades)		
Material	STEEL	STEEL
Diameter	14 1/2	14 1/2

Always wear a helmet, eye protection and protective proper clothing.
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

