



The "Africa" 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.

F40JMHDL



TECHNICAL CHARACTERISTICS	F40JMHDL
MOTOR	
Engine Type	In-line 4
Ignition System	Electronic Ignition (TCI)
Reduction ratio	9.4 :1
Start-up	Electric with Prime Start™
Power system	3 carburetors
Lubrication system	Unleaded
Fuel consumption (L/h-tr/min)	15.2 L/h @5500 r/min
Fuel	Wet Sump
Full throttle operating range (tr/min)	5000-6000
Max.Prop Shaft Horsepower (Kw)	29.4 (40 hp)
Bore x Stroke (mm)	65.0 X 75.0
Architecture	L3
Displacement (cc)	747
MORE	
Propeller Rotation	Clockwise
Alternator	14 A
Control	Remote Control
DIMENSIONS	
Dry weight with propeller (kg)	95
Engine transom height (mm)	L: 536 (21.1 inch)
Oil capacity (L)	1.7 L / 1.5 L
EQUIPMENTS	
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
Kill Switch	✓
REGULAR PROPELLER (3 blades)	
Material	ALUMINUM
Diameter	11 3/8



Always wear a helmet, eye protection and protective proper clothing.
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

