



## F50DETL

The "Africa" 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F50DETL
<b>MOTOR</b>	
Engine Type	In-line 4
Ignition System	Electronic Ignition (TCI)
Reduction ratio	9.3:1
Start-up	Electric with Prime Start™
Power system	4 carburetors
Lubrication system	Unleaded
Fuel consumption (L/h-tr/min)	15.7 L/h @5500 r/min
Fuel	Wet Sump
Full throttle operating range (tr/min)	5000-6000
Max.Prop Shaft Horsepower (Kw)	36.8 (50 hp)
Bore x Stroke (mm)	63.0 X 75.0
Architecture	L4
Displacement (cc)	935
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	10 A
Control	Remote Control
<b>DIMENSIONS</b>	
Dry weight with propeller (kg)	110
Engine transom height (mm)	L: 533 (21.0 inch)
Oil capacity (L)	2.2 L/2.0 L
<b>EQUIPMENTS</b>	
Service kit assy.	✓
Fuel Tank comp.	✓
Remocon Control	✓
15ft Cable Remocon	✓
Tachometer	✓
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	11 1/8



Always wear a helmet, eye protection and protective proper clothing.  
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

