



## FT50CETL/FT50CETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	FT50CETL	FT50CETX
<b>MOTOR</b>		
Engine Type	In-line 4	In-line 4
Ignition System	Electronic Ignition (TCI)	Injection Électronique (EFI)
Reduction ratio	9.3 :1	9.3 :1
Start-up	Electric with Prime Start™	Electric with Prime Start™
Power system	4 carburators	4 carburetors
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	16.0 L/h @5500 r/min	16.0 L/h @5500 r/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	5000-6000	5000-6000
Max.Prop Shaft Horsepower (Kw)	36.8 (50 hp)	36.8 (50 hp)
Bore x Stroke (mm)	63.0 X 75.0	63.0 X 75.0
Architecture	L4	L4
Displacement (cc)	935	935
<b>MORE</b>		
Propeller Rotation	Clockwise	Clockwise
Alternator	10 A	10 A
Control	Remote Control	Remote Control
<b>DIMENSIONS</b>		
Dry weight with propeller (kg)	121	121
Engine transom height (mm)	L: 536 (21.1 inch)	X: 647 (25.5 inch)
Oil capacity (L)	2.2 L / 2.0 L	2.2 L / 2.0 L
<b>EQUIPMENT</b>		
Service kit assy.	✓	✓
Fuel Tank comp.	✓	✓
Remocon Control	✓	✓
Tachometer	✓	✓
<b>REGULAR PROPELLER (3 blades)</b>		
Material	ALUMINUM	ALUMINUM
Diameter	13 5/8	13 5/8

Always wear a helmet, eye protection and protective proper clothing.  
CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

