



## E150AETX

The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.



TECHNICAL CHARACTERISTICS	E150AETX
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	6.2 :1
Start-up	Electric
Power system	3 Dual Throat Carburetors
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	72 l/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	110.3 (150 hp)
Bore x Stroke (mm)	90.0 X 68.0
Architecture	V6
Displacement (cc)	2596
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	14 A
Control	Remote Control
<b>DIMENSIONS</b>	
Engine transom height (mm)	X : 642 (25.3 in)
Dry weight with propeller (kg)	184

Always wear a helmet, eye protection and protective proper clothing.

CICA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

